

## 5.2 Signalling a Specific Release Profile

## 5.2.1 ReleaseProfileVersionId attribute

To indicate in the `NewReleaseMessage` the use of a specific Profile, the `ReleaseProfileVersionId` attribute on the root tag of the message shall be set as defined in column 2 of the table in [Clause 5.1 \(Definition of Release Profiles\)](#).

For the avoidance of doubt, the above is only valid for a `NewReleaseMessage` in accordance with Version 4 or above of the [Electronic Release Notification Message Suite Standard](#).

**Note:** `ReleaseProfileVersionId` may not include any white-space characters.

## 5.2.2 ReleaseProfileVersionVariantId attribute

If the `NewReleaseMessage` uses of a specific Profile Variant, the `ReleaseProfileVariantVersionId` attribute on the root tag of the message shall be set as follows:

```
yyy[ yyy]*
```

With "yyy" being the name of the profile variant as defined in [Clause 5.5 \(Rules for Release Profile Variants\)](#). Multiple variants shall be separated by a space character.

A profile may only be combined with those variants listed in the last column in the table in [Clause 5.1 \(Definition of Release Profiles\)](#). Multiple variants can be communicated as shown below. They must be communicated in the order defined in [Clause 5.5 \(Rules for Release Profile Variants\)](#).

For the avoidance of doubt, the above is only valid for a `NewReleaseMessage` in accordance with Version 4 or above of the [Electronic Release Notification Message Suite Standard](#).

**Note:** `ReleaseProfileVersionVariantId` may not include any white-space characters other than to separate multiple variants.